







STA  
TUS

Table with columns: SIZE, SCULP, LR, ISO, PR, SLR, OD, FREE WIDTH, LOADED WIDTH, RIM1, RIM2, RIM3, FLAP, TUBE, RPM, MAX SINGLE, MAX DUAL, MPH, TRD WDT, UND TRD, ARC RAD, SEC HGT, MIN DUAL SPACE, CONTACT PATCH (GROSS, NET, PSI), FOOT PRINT (LTH, WTH, WT, #), ASSY (WT, CAI, MSPN). Rows include various part numbers like A 365/80R20, L 365/80R20, etc.



















STATUS

STATUS	SIZE	SCULP	LR	ISO	PR	SLR	OD	FREE WIDTH (IN)	LOADED WIDTH (IN)	RIM1	RIM2	RIM3	FLAP	TUBE	RPM	MAX SINGLE		MAX DUAL		TRD WDT (IN)	UND TRD (/32)	T/D (/32)	ARC RAD (IN)	SEC HGT (IN)	MIN DUAL SPACE (IN)	CONTACT PATCH			FOOT PRINT		ASSY		CAI	MSPN		
																LOAD	PSI	LOAD	PSI							MPH	GROSS IN^2	NET IN^2	PSI	LTH (IN)	WTH (IN)	WT #			WT #	
A	275/80R24.5	XDA3	G	144/141	K	14	19.5	41.9	10.7	11.8	8.25	7.50	-	NA	TBLS	495	6175	110	5675	110	75	8.5	6.3	25.8	8.7	12.1	76.9	53.5	100	9.6	8.4	129.0		721235	68934	
A	275/80R24.5	XDHT	G	144/141	K	14	19.5	41.9	10.7	11.7	8.25	7.50	-	NA	TBLS	496	6175	110	5675	110	75	8.5	6.9	27.7	31.5	8.7	12.1	75.0	49.4	100	9.8	8.4	130.0		022424	13196
L	275/80R24.5	XDN	G	NA/NA	-	14	19.4	41.5	10.8	11.8	8.25	7.50	-	NA	TBLS	500	6175	110	5675	110	75		7.6	25.2		8.5	12.2						119.5		023861	43744
A	275/80R24.5	XDN2	G	NA/NA	-	14	19.6	41.8	10.6	11.7	8.25	7.50	-	NA	TBLS	495	6175	110	5675	110	75	9.6		26.7		8.6	12.2	80.2	59.1	110	8.9	9.3	130.5		148791	75684
+	275/80R24.5	XM+S4	G	144/141	K	14	19.3	41.6	10.8		8.25	7.50	-	NA	TBLS	473	6610	105	6005	105	75	7.7	7.6	22.7	27.6	8.5	12.1	71.8	44.1	100	9.6	7.6	116.0		022390	03724
A	275/80R24.5	XT-1	G	144/141	K	14	19.1	40.8	10.8	11.9	8.25	7.50	-	NA	TBLS	501	6175	110	5675	110	75	8.6	6.9	12.0	21.1	8.3	12.4	76.2	56.3	100	9.6	8.5	110.3		022582	29684
+	275/80R24.5	XTA ENERGY	G	NA/NA	-	14					8.25	7.50	-	NA	TBLS		6175	110	5675	110	75		12.7									116.9	204.0	148716	73152	
A	275/80R24.5	XTE	G	NA/NA	-	14	19.2	41.2	10.8		8.25	7.50	-	NA	TBLS	504	6175	110	5675	110	75	9.0					12.2					105.4		693082	40644	
A	275/80R24.5	XZA 3	G	144/141	K	14	19.3	41.3	10.7	11.7	8.25	7.50	-	NA	TBLS	501	6175	110	5675	110	75			19.0		8.4	12.1	7.0	5.5	100	8.8	8.7	115.5		975660	73173
A	275/80R24.5	XZA-1+	G	144/141	K	14	19.3	41.3	10.7	11.7	8.25	7.50	-	NA	TBLS	501	6175	110	5675	110	75	8.0	7.6	18.0	27.6	8.4	12.2	69.7	50.6	100	9.3	7.9	116.0		023314	30968
A	275/80R24.5	XZA-1B	G	144/141	K	14	19.3	41.3	10.7	11.7	8.25	7.50	-	NA	TBLS	501	6175	110	5675	110	75	8.0	7.6	18.0	27.6	8.4	12.2	69.7	50.6	100	9.3	7.9	116.0		742910	89975
A	275/80R24.5	XZA2	G	144/141	K	14	19.2	41.3	10.6	11.7	8.25	7.50	-	NA	TBLS	503	6175	110	5675	110	75	8.7	6.9	17.9	17.3	8.4	12.3	75.4	61.1	100	9.4	8.3	115.1		023894	78216
A	275/80R24.5	XZE	G	NA/NA	-	14	19.3	41.3	10.8	11.8	8.25	7.50	-	NA	TBLS	502	6175	110	5675	110	75	8.6	6.0	22.0	21.1	8.2	12.2	76.2	59.1	100	9.3	8.3	118.0		023788	57425
A	275/80R24.5	XDA-HT	G	144/141	K	14	19.5	42.0	10.7	11.8	8.25	7.50	-	NA	TBLS	495	6175	110	5675	110	75	8.5	6.3	30.0		8.7	12.2						133.6		148739	55519
+	305/75R24.5	XDA	H	152/148	L	16	20.0	42.9	11.7	12.9	8.25	9.00	-	NA	TBLS	483	7830	115	6940	115	65	10.2	8.2	25.6	23.0	9.2	13.2	90.1	60.0	115	10.3	9.9	157.4		109294	09248
A	305/75R24.5	XDA-HT	J	NA/NA	-	18	20.1	43.2	11.5	12.7	8.25	9.00	-	NA	TBLS	493	8270	120	7160	120	75	10.0	6.9	29.0	26.2	9.4	13.0	93.5	63.2	120	10.4	9.7	154.9		904171	86424
+	305/75R24.5	XZA	H	152/148	L	16	19.9	42.4	11.7	12.9	8.25	9.00	-	NA	TBLS	484	7830	115	6940	115	65	9.2	8.2	18.9	24.0	9.0	13.2	84.0	54.7	123	10.1	9.1	143.3		109212	09450
A	305/75R24.5	XZE2	J	154/149	K	18	19.8	42.7	11.6	12.7	8.25	9.00	-	NA	TBLS	486	8270	120	7160	120	65	9.9		22.0			13.0	92.5	75.1		9.8	9.8	145.5		594768	67251

**LEGEND:**

- \* - OBSOLETE
- + - NOT AVAILABLE
- A - AVAILABLE
- L - LIMITED AVAILABILITY
- P - PRELIMINARY
- S - STUDY TIRES